

ECIA

PUBLICATION

ECIA Guidelines for Packing and Dunnage of Electronic Components

NIGP 108.00

September 1996

ELECTRONIC COMPONENTS INDUSTRY ASSOCIATION

Industry Guidelines

NOTICE

ECIA Industry Guidelines and Publications contain material that has been prepared, progressively reviewed, and approved through various ECIA-sponsored industry task forces, comprised of ECIA member distributors and manufacturers, and subsequently reviewed and approved by the ECIA Board of Directors. After adoption, efforts are taken to ensure widespread dissemination of the guidelines. ECIA reviews and updates the guidelines as needed.

ECIA Industry Guidelines and Publications are designed to serve the public interest, including electronic component distributors, through the promotion of uniform and consistent practices between manufacturers and distributors resulting in improved efficiency, profitability, product quality, safety, and environmentally responsible practices. Existence of such guidelines shall not in any respect preclude any member or non-member of ECIA from adopting any other practice not in conformance to such guidelines, nor shall the existence of such guidelines preclude their voluntary use by those other than ECIA members, whether the guideline is to be used either domestically or internationally.

ECIA does not assume any liability or obligation whatever to parties adopting ECIA Industry Guidelines and Publications. Each company must independently assess whether adherence to some or all of the guidelines is in its own best interest.

Inquiries, comments and suggestions relative to the content of this ECIA Industry Guideline should be addressed to ECIA headquarters.

Published by

NATIONAL ELECTRONIC DISTRIBUTORS ASSOCIATION
1111 Alderman Drive, Suite 400
Alpharetta, GA 30005
(678) 393-9990

Copyright 1996
Printed in U.S.A.
All rights reserved

ECIA thanks the following distributors and manufacturers for their participation in the task force which developed these guidelines:

AMP, Inc.	Marsh Electronics
Arrow Electronics, Inc.	Marshall Industries
Avnet Inc.	Murata Electronics N.A.
AVX, Inc.	Newark Electronics
Bell Industries	Panduit Corporation
Bourns, Inc.	Philips Components
Capstone Electronics	Priebe Electronics, Inc.
Hammond Electronics	Projections Unlimited, inc.
Joseph Electronics	RS Electronics
Kent Electronics	T.T.I., Inc.

1.0 PURPOSE

The purpose of this document is to provide distributors and manufacturers with guidelines for the packing and dunnage of connectors, electromechanical devices, passive components, and commercial semiconductors.

2.0 SCOPE

Compliance with these guidelines is voluntary. These guidelines may be specified as a requirement by either the distributor or the customer. They are not intended to replace or supersede any military specifications, regulations of the Interstate Commerce commission, or other regulatory agency requirements.

3.0 REFERENCE DOCUMENT

* EIA 625: "Requirements for Handling Electrostatic Discharge Sensitive Devices"

4.0 DEFINITIONS

4.1 UNIT CONTAINER: The first container applied to a single or several components. For purposes of these guidelines, examples of unit containers are tubes, rails, trays, reels, or bags containing the components.

4.2 INTERMEDIATE CONTAINER: A wrap, box, bag, or bundle that contains one or more unit containers of identical items.

4.3 SHIPPING CONTAINER: A container intended for transportation of the product.

4.4 UNIT LOAD: A number of filled shipping containers or other items held together by one or more means such as a pallet, stretch wrap, shrink wrap or strapping.

5.0 PACKING

5.1 GENERAL REQUIREMENTS: All packing should provide protection for the product from, but not limited to:

- 5.1.1 bent leads
- 5.1.2 damage by abrasion
- 5.1.3 contamination
- 5.1.4 light amounts of moisture that could damage product
- 5.1.5 prevention of ancillary hardware loss during shipment
- 5.1.6 package bursting from inertia or weight
- 5.1.7 ESD, preferred

5.2. All packing should ensure safe handling, shipping, and storage of the product.

5.3. The unsupported bottom of a manually-handled container should be able to hold its contents.

5.4. Each manually-handled individual shipping container should not exceed thirty-five (35) pounds. Manually handled containers that exceed 35 pounds should be labeled to indicate that its weight exceeds 35 pounds. This label should be highly visible and located near the shipping label.

6.0 MATERIALS

6.1. Packing materials should be made of non-ozone depleting substances (CFC free).

6.2 The use of non-static generating packing materials is required* for ESD sensitive product unit containers, and encouraged for all other product.

6.3 When possible, packing and dunnage materials should be made of recycled materials. Every effort should be made to use materials for packing and dunnage that can be recycled.

6.4 All packing should be free of handling hazards such as protruding nails, staples, or non-secure banding.

6.5 Shipping containers should be sealed with adequate gummed tape or pressure sensitive tape. Use of staples, glue, or metal fasteners for container closure should be avoided.

*Reference EIA 625

6.6 Dunnage and void fill made of kraft paper, antistatic bubble wrap, or antistatic polypropylene or polyethylene foam are preferred. Use of sawdust, wood shavings, excelsior, shredded paper, shredded corrugated board, edible popcorn, newsprint, bagged (non-biodegradable) foam, and loose or free flow materials such as peanuts should be avoided.

When dunnage is needed for ESD (Electrostatic Discharge Sensitive) devices that are not within a protected barrier, static resistant bubble pack is preferred.

6.7 The preferred method to secure unit loads is stretch wrap. When banding is required, the use of metal banding should be avoided.

6.8. The preferred shipping carton is unbleached corrugated.

6.9 The preferred pallet sizes are 42" X 48" or 40" X 48", with a minimum clearance between the top and bottom decks of 3.5". The use of skids (no bottom deck) should be avoided. The preferred pallet materials are wood or corrugated.